

PATENT
PD-200335

MULTIPLE NONVOLATILE MEMORIES

Inventors:

Ronald Cocchi
Christopher P. Curren
Raynold M. Kahn

20032201 1005511 022302

MULTIPLE NONVOLATILE MEMORIES

CROSS-REFERENCE TO RELATED APPLICATIONS

5 [0001] This application is related to the following co-pending and commonly-assigned patent applications, which applications are incorporated by reference herein:

[0002] United States Patent Application Serial No. xx/xxx,xxx, entitled "DEDICATED NONVOLATILE MEMORY", by Ronald Cocchi, et. al., Attorney Docket No. PD-200337, filed on the same date herewith;

10 [0003] United States Patent Application Serial No. xx/xxx,xxx, entitled "HIDDEN IDENTIFICATION", by Ronald Cocchi, et. al., Attorney Docket No. PD-200336, filed on the same date herewith; and

[0004] United States Patent Application Serial No. xx/xxx,xxx, entitled "ASYNCHRONOUS CONFIGURATION", by Ronald Cocchi, et. al., Attorney Docket No. PD-201161, filed on the same date herewith.

BACKGROUND OF THE INVENTION

1. Field of the Invention

[0005] The present invention relates to systems and methods for preventing unauthorized access to digital services and in particular to a method and system for distributing multiple nonvolatile memory components to provide additional security for accessing digital services.

2. Description of the Related Art

[0006] Digital services such as television programs and information regarding those programs (e.g., a program guide) are distributed to users by a variety of broadcasting methods. Such services may be proprietary and available on a subscription basis. To prevent unauthorized access to the services, a plethora of security mechanisms are utilized. Such mechanisms may store information in memory, wherein the information is used to validate a user or provide access. However, persons often attempt to obtain illegal/unauthorized access to the services by altering the memory contents. What is needed is the capability to prevent or increase the

difficulty of obtaining illegal access to the information and digital services. These problems may be better understood by a description of current broadcasting methods, security mechanisms, and methods for obtaining unauthorized access to such services.

208220 FEB 5800T
[0007] As described above, television programs and digital services are distributed to viewers
5 by a variety of broadcasting methods. These methods include traditional analog broadcast television (National Television Systems Committee or "NTSC" standard), the soon to be required digital broadcast television (Advanced Television Systems Committee or "ATSC" standard), cable television (both analog and digital), satellite broadcasting (both analog and digital), as well as other methods. These methods allow channels of television content to be
10 multiplexed and transmitted over a common transmission medium.

[0008] To view the television programming and have access to the digital services, users commonly have a set top box (also referred to as an integrated receiver/decoder [IRD]). Within the system or set top box, a security component/microcircuit known as a smart card may be utilized to prevent unauthorized access to the television programs and digital services. The
15 smart card microcircuit may contain a microprocessor, volatile memory components, a nonvolatile memory component, and a system input/output module.

[0009] Nonvolatile memory has been used extensively throughout the electronics industry. For example, in the IRD, the microprocessor utilizes nonvolatile memory to contain state information (e.g., status information) used to provide the desired functionality and enforce
20 security policies intended by the designers. The microprocessor and/or a memory access control unit utilized by the microprocessor restricts access to the memory components.

[0010] However, there have been numerous attempts by individuals or companies (i.e., hackers or attackers) to attack, misuse or modify the nonvolatile memory through external means of reprogramming or otherwise altering the contents of the memory when the memory
25 components have been misused or access control has been subverted. For example, attacks using unforeseen methods or subverting poorly implemented defenses can be used to gain unauthorized access to the contents of the memory and/or lead to reprogramming the contents

of the memory. Reprogramming or unauthorized access to the memory contents can lead to complete compromise of the security features intended in the device.

[0011] The simplest and most prevalent form of attack against the memory components uses external means using a system's input/output module due to the low cost of the equipment

- 5 required to implement this form of attack. Once the single memory component has been breached, the attacker may then have the capability to access all memory address locations that reside other memory components.

SUMMARY OF THE INVENTION

- 10 [0012] Digital service systems often contain a security component known as a smart card that prevents unauthorized access to the digital services. The smart card contains a microprocessor, memory components, a custom logic block, and a system input/output module. The security system may be compromised if components are attacked or used in unintended ways.

- [0013] One or more embodiments of the invention provide for separating storage and address
15 space for nonvolatile memory storage (such as EEPROM, EPROM, or batter backed RAM) through duplicating multiple nonvolatile memory components and placing them on the system bus. The microprocessor has full access to and complete control over each nonvolatile memory storage unit. Initialization, programming, and testing may be conducted separately and uniquely for each memory component.

20

BRIEF DESCRIPTION OF THE DRAWINGS

[0014] Referring now to the drawings in which like reference numbers represent corresponding parts throughout:

[0015] FIG. 1 is a diagram showing an overview of a video distribution system;

- 25 [0016] FIG. 2 is a block diagram showing a typical uplink configuration showing how video program material is uplinked to a satellite for transmission to subscribers using a single transponder;

[0017] FIG. 3 is a block diagram of one embodiment of the program guide subsystem;

[0018] FIG. 4A is a diagram of a representative data stream received from a satellite;

[0019] FIG. 4B is a diagram illustrating the structure of a data packet;

[0020] FIG. 5 is a block diagram of one embodiment of an integrated receiver/decoder;

[0021] FIG. 6 illustrates the architecture of a conditional access module in accordance with

5 one or more embodiments of the invention; and

[0022] FIG. 7 is a flow chart illustrating the use of multiple nonvolatile memory components in accordance with one or more embodiments of the invention.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

10 [0023] In the following description reference is made to the accompanying drawings which form a part hereof and which show, by way of illustration, several embodiments of the present invention. It is understood that other embodiments may be utilized and structural changes may be made without departing from the scope of the present invention.

15 Video Distribution System

[0024] FIG. 1 is a diagram illustrating an overview of a single satellite video distribution system 100. The video distribution system 100 comprises a control center 102 in communication with an uplink center 104 via a ground or other link 114 and with a subscriber receiver station 110 via a public switched telephone network (PSTN) or other link 120. The control center 102 provides program material (e.g. digital services, video programs, audio programs and data) to the uplink center 104 and coordinates with the subscriber receiver stations 110 to offer, for example, pay-per-view (PPV) program services, including billing and associated decryption of video programs.

20 [0025] The uplink center 104 receives program material and program control information from the control center 102, and using an uplink antenna 106 and transmitter 105, transmits the program material and program control information to the satellite 108 via uplink 116. The satellite receives and processes this information, and transmits the video programs and control information to the subscriber receiver station 110 via downlink 118 using transmitter 107. The

subscriber receiving station 110 receives this information using the outdoor unit (ODU) 112, which includes a subscriber antenna and a low noise block converter (LNB).

[0026] The subscriber receiving station 110 permits the use/viewing of the information by a subscriber 122. For example, the information may be used/viewed on a television 124 or other display device. To control access to the information, the subscriber receiving station 110 includes an integrated receiver/decoder (IRD) 126. In embodiments of the invention, the IRD 126 is communicatively coupled to a security component known as a conditional access model or smart card that controls access to the information/digital services.

[0027] In one embodiment, the subscriber receiving station antenna is an 18-inch slightly oval-shaped Ku-band antenna. The slight oval shape is due to the 22.5 degree offset feed of the LNB (low noise block converter) which is used to receive signals reflected from the subscriber antenna. The offset feed positions the LNB out of the way so it does not block any surface area of the antenna minimizing attenuation of the incoming microwave signal.

[0028] The video distribution system 100 can comprise a plurality of satellites 108 in order to provide wider terrestrial coverage, to provide additional channels, or to provide additional bandwidth per channel. In one embodiment of the invention, each satellite comprises 16 transponders to receive and transmit program material and other control data from the uplink center 104 and provide it to the subscriber receiving stations 110. Using data compression and multiplexing techniques the channel capabilities, two satellites 108 working together can receive and broadcast over 150 conventional (non-HDTV) audio and video channels via 32 transponders.

[0029] While the invention disclosed herein will be described with reference to a satellite-based video distribution system 100, the present invention may also be practiced with terrestrial-based transmission of program information, whether by broadcasting means, cable, or other means. Further, the different functions collectively allocated among the control center 102 and the uplink center 104 as described above can be reallocated as desired without departing from the intended scope of the present invention.

5

10

15

20

25

204A-204F (collectively referred to hereinafter as packetizer(s) 204) associated with each source 200.

[0034] The data packets are assembled using a reference from the system clock 214 (SCR), and from the conditional access manager 210, which provides the SCID to the packetizers 204 for use in generating the data packets. These data packets are then multiplexed into serial data and transmitted.

Program Guide Subsystem

[0035] FIG. 3 is a block diagram of one embodiment of the program guide subsystem 206.

The program guide data transmitting system 206 includes program guide database 302, compiler 304, sub-databases 306A-306C (collectively referred to as sub-databases 306) and cyclers 308A- 308C (collectively referred to as cyclers 308).

[0036] Schedule feeds 310 provide electronic schedule information about the timing and content of various television channels, such as that found in television schedules contained in newspapers and television guides. Schedule feeds 310 preferably include information from one or more companies that specialize in providing schedule information, such as TRIBUNE MEDIA SERVICES™, and T.V. DATA™. The data provided by companies such as TRIBUNE MEDIA SERVICES™ and T.V. DATA™ are typically transmitted over telephone lines to program guide database 302. These companies provide television schedule data for all of the television stations across the nation plus the nationwide channels, such as SHOWTIME™, HBO™, and the DISNEY CHANNEL™. The specific format of the data that are provided by these companies varies from company to company. Program guide database 302 preferably includes schedule data for television channels across the entire nation including all nationwide channels and local channels, regardless of whether the channels are transmitted by the transmission station.

[0037] Program guide database 302 is a computer-based system that receives data from schedule feeds 310 and organizes the data into a standard format. Compiler 304 reads the standard form data out of program guide database 302, identifies common schedule portions,

converts the program guide data into the proper format for transmission to users (specifically, the program guide data are converted into objects as discussed below) and outputs the program guide data to one or more of sub-databases 306.

[0038] Program guide data can also be manually entered into program guide database 302

5 through data entry station 312. Data entry station 312 allows an operator to enter additional scheduling information, as well as combining and organizing data supplied by the scheduling companies. As with the computer organized data, the manually entered data are converted by the compiler into separate objects and sent to one or more of sub-databases 306.

[0039] The program guide objects are temporarily stored in sub-databases 306 until cyclers

10 308 request the information. Each of cyclers 308 may transmit objects at a different rate than the other cyclers 308. For example, cycler 308A may transmit objects every second, while cyclers 308B and 308C may transmit objects every 5 seconds and every 10 seconds, respectively.

[0040] Since the subscriber's receivers may not always be on and receiving and saving

15 objects, the program guide information is continuously re-transmitted. Program guide objects for programs that will be shown in the next couple of hours are sent more frequently than program guide objects for programs that will be shown later. Thus, the program guide objects for the most current programs are sent to a cycler 308 with a high rate of transmission, while program guide objects for later programs are sent to cyclers 308 with a lower rate of
20 transmission. One or more of the data outputs 314 of the cyclers 308 are forwarded to the packetizer of a particular transponder, as depicted in FIG. 2.

[0041] It is noted that the uplink configuration depicted in FIG. 2 and the program guide subsystem depicted in FIG. 3 can be implemented by one or more hardware modules, one or more software modules defining instructions performed by a processor, or a combination of
25 both.

Broadcast Data Stream Format and Protocol

- [0042] FIG. 4A is a diagram of a representative data stream. The first packet segment 402 comprises information from video channel 1 (data coming from, for example, the first video program source 200A). The next packet segment 404 comprises computer data information that was obtained, for example from the computer data source 208. The next packet segment 406 comprises information from video channel 5 (from one of the video program sources 200). The next packet segment 408 comprises program guide information such as the information provided by the program guide subsystem 206. As shown in FIG. 4A, null packets 410 created by the null packet module 212 may be inserted into the data stream as desired.
- 10 [0043] The data stream therefore comprises a series of packets from any one of the data sources in an order determined by the controller 216. The data stream is encrypted by the encryption module 218, modulated by the modulator 220 (typically using a QPSK modulation scheme), and provided to the transmitter 222, which broadcasts the modulated data stream on a frequency bandwidth to the satellite via the antenna 106. The receiver 126 receives these
- 15 signals, and using the SCID, reassembles the packets to regenerate the program material for each of the channels.
- [0044] FIG. 4B is a diagram of a data packet. Each data packet (e.g. 402-416) is 147 bytes long, and comprises a number of packet segments. The first packet segment 420 comprises two bytes of information containing the SCID and flags. The SCID is a unique 12-bit number
- 20 that uniquely identifies the data packet's data channel. The flags include 4 bits that are used to control other features. The second packet segment 422 is made up of a 4-bit packet type indicator and a 4-bit continuity counter. The packet type identifies the packet as one of the four data types (video, audio, data, or null). When combined with the SCID, the packet type determines how the data packet will be used. The continuity counter increments once for each
- 25 packet type and SCID. The next packet segment 424 comprises 127 bytes of payload data, which in the cases of packets 402 or 406 is a portion of the video program provided by the video program source 200. The final packet segment 426 is data required to perform forward error correction.

Integrated Receiver/Decoder

[0045] FIG. 5 is a block diagram of an integrated receiver/decoder (IRD) 126 (also hereinafter alternatively referred to as receiver 126 or a set top box). The receiver 126 comprises a tuner/demodulator 504 communicatively coupled to an ODU 112 having one or more LNBs 502. The LNB 502 converts the 12.2- to 12.7 GHz downlink 118 signal from the satellites 108 to, e.g., a 950-1450 MHz signal required by the IRD's 126 tuner/demodulator 504. The LNB 502 may provide either a dual or a single output. The single-output LNB 502 has only one RF connector, while the dual output LNB 502 has two RF output connectors and can be used to feed a second tuner 504, a second receiver 126, or some other form of distribution system.

[0046] The tuner/demodulator 504 isolates a single, digitally modulated 24 MHz transponder, and converts the modulated data to a digital data stream. The digital data stream is then supplied to a forward error correction (FEC) decoder 506. This allows the IRD 126 to reassemble the data transmitted by the uplink center 104 (which applied the forward error correction to the desired signal before transmission to the subscriber receiving station 110) verifying that the correct data signal was received, and correcting errors, if any. The error-corrected data may be fed from the FEC decoder module 506 to the transport module 508 via an 8-bit parallel interface.

[0047] The transport module 508 performs many of the data processing functions performed by the IRD 126. The transport module 508 processes data received from the FEC decoder module 506 and provides the processed data to the video MPEG decoder 514 and the audio MPEG decoder 517. In one embodiment of the present invention, the transport module, video MPEG decoder and audio MPEG decoder are all implemented on integrated circuits. This design promotes both space and power efficiency, and increases the security of the functions performed within the transport module 508. The transport module 508 also provides a passage for communications between the microcontroller 510 and the video and audio MPEG decoders 514, 517. As set forth more fully hereinafter, the transport module also works with the

conditional access module (CAM) 512 to determine whether the subscriber receiving station 110 is permitted to access certain program material/digital services. Data from the transport module can also be supplied to external communication module 526.

5 [0048] The CAM 512 functions in association with other elements to decode an encrypted signal from the transport module 508. The CAM 512 may also be used for tracking and billing these services. In one embodiment of the present invention, the CAM 512 is a smart card, having contacts cooperatively interacting with contacts in the IRD 126 to pass information. In order to implement the processing performed in the CAM 512, the IRD 126, and specifically the transport module 508 provides a clock signal to the CAM 512. Details of the CAM 512
10 architecture are described below.

[0049] Video data is processed by the MPEG video decoder 514. Using the video random access memory (RAM) 536, the MPEG video decoder 514 decodes the compressed video data and sends it to an encoder or video processor 516, which converts the digital video information received from the video MPEG module 514 into an output signal usable by a display
15 124 or other output device. By way of example, processor 516 may comprise a National TV Standards Committee (NTSC) or Advanced Television Systems Committee (ATSC) encoder. In one embodiment of the invention both S-Video and ordinary video (NTSC or ATSC) signals are provided. Other outputs may also be utilized, and are advantageous if high definition programming is processed.

20 [0050] Audio data is likewise decoded by the MPEG audio decoder 517. The decoded audio data may then be sent to a digital to analog (D/A) converter 518. In one embodiment of the present invention, the D/A converter 518 is a dual D/A converter, one for the right and left channels. If desired, additional channels can be added for use in surround sound processing or secondary audio programs (SAPs). In one embodiment of the invention, the dual D/A
25 converter 518 itself separates the left and right channel information, as well as any additional channel information. Other audio formats may similarly be supported. For example, other audio formats such as multi-channel DOLBY DIGITAL AC-3 may be supported.

[0051] A description of the processes performed in the encoding and decoding of video streams, particularly with respect to MPEG and JPEG encoding/decoding, can be found in Chapter 8 of "Digital Television Fundamentals," by Michael Robin and Michel Poulin, McGraw-Hill, 1998, which is hereby incorporated by reference herein.

5 [0052] The microcontroller 510 receives and processes command signals from the remote control 524, an IRD 126 keyboard interface, and/or another input device. The microcontroller receives commands for performing its operations from a processor programming memory, which permanently stores such instructions for performing such commands. The processor programming memory may comprise a read only memory (ROM) 538, an electrically erasable
10 programmable read only memory (EEPROM) 522 or, similar memory device. The microcontroller 510 also controls the other digital devices of the IRD 126 via address and data lines (denoted "A" and "D" respectively, in FIG. 5).

[0053] The modem 540 connects to the customer's phone line via the PSTN port 120. It calls, e.g. the program provider, and transmits the customer's purchase information for billing
15 purposes, and/or other information. The modem 540 is controlled by the microprocessor 510. The modem 540 can output data to other I/O port types including standard parallel and serial computer I/O ports.

[0054] The present invention also comprises a local storage unit such as the video storage device 532 for storing video and/or audio data obtained from the transport module 508. Video
20 storage device 532 can be a hard disk drive, a read/writable compact disc of DVD, a solid state RAM, or any other storage medium. In one embodiment of the present invention, the video storage device 532 is a hard disk drive with specialized parallel read/write capability so that data may be read from the video storage device 532 and written to the device 532 at the same time. To accomplish this feat, additional buffer memory accessible by the video storage
25 532 or its controller may be used. Optionally, a video storage processor 530 can be used to manage the storage and retrieval of the video data from the video storage device 532. The video storage processor 530 may also comprise memory for buffering data passing into and out of the video storage device 532. Alternatively or in combination with the foregoing, a plurality

of video storage devices 532 can be used. Also alternatively or in combination with the foregoing, the microcontroller 510 can also perform the operations required to store and or retrieve video and other data in the video storage device 532.

[0055] The video processing module 516 input can be directly supplied as a video output to a viewing device such as a video or computer monitor. In addition, the video and/or audio outputs can be supplied to an RF modulator 534 to produce an RF output and/or 8 vestigial side band (VSB) suitable as an input signal to a conventional television tuner. This allows the receiver 126 to operate with televisions without a video output.

[0056] Each of the satellites 108 comprises a transponder, which accepts program information from the uplink center 104, and relays this information to the subscriber receiving station 110. Known multiplexing techniques are used so that multiple channels can be provided to the user. These multiplexing techniques include, by way of example, various statistical or other time domain multiplexing techniques and polarization multiplexing. In one embodiment of the invention, a single transponder operating at a single frequency band carries a plurality of channels identified by respective service channel identification (SCID).

[0057] Preferably, the IRD 126 also receives and stores a program guide in a memory available to the microcontroller 510. Typically, the program guide is received in one or more data packets in the data stream from the satellite 108. The program guide can be accessed and searched by the execution of suitable operation steps implemented by the microcontroller 510 and stored in the processor ROM 538. The program guide may include data to map viewer channel numbers to satellite transponders and service channel identifications (SCIDs), and also provide TV program listing information to the subscriber 122 identifying program events.

[0058] The functionality implemented in the IRD 126 depicted in FIG. 5 can be implemented by one or more hardware modules, one or more software modules defining instructions performed by a processor, or a combination of both.

Access Card

[0059] A CAM 512 often contains a microprocessor, memory components (a volatile component and a nonvolatile component) and a system input/output module to communicate with transport 508. Traditional microprocessors within a CAM 512 have nonvolatile memory to contain state that is used to provide the desired functionality and enforce security policies intended by the designers. The microprocessor and/or memory access control unit restricts access to the memory components.

[0060] As described above, attacks may use unforeseen methods or may subvert poorly implemented defenses to gain unauthorized access to the contents of the memory and/or lead to reprogramming the contents of the memory. For example, most attacks occur by inappropriate manipulation of the microprocessor or memory access control unit. Reprogramming or unauthorized access to the memory contents can lead to complete compromise of the security features intended in the CAM 512. The simplest and most prevalent form of attack against the memory component uses external means using the system input/output module due to the low cost of the equipment required to implement this form of attack.

[0061] To avoid this method of attack, access to the nonvolatile memory components is distributed among several physically separate and independently controlled nonvolatile memory components. Using this approach, it may not be possible to compromise one nonvolatile memory component and march through all memory address locations that reside other memory components. Only the attacked memory component is compromised.

[0062] FIG. 6 illustrates the architecture of a CAM 512 in accordance with one or more embodiments of the invention. The CAM 512 contains a microprocessor 602, volatile memory components 604 (e.g., random access memory [RAM]), a plurality of nonvolatile memory components 606 (e.g., electrical erasable programmable read only memory [EEPROM], erasable programmable read only memory [EPROM], or batter packed RAM), and a system input/output module 608, all of which are communicatively coupled to a system bus 610. As illustrated, a plurality of nonvolatile memory components 606 are utilized. Using this approach, each nonvolatile memory component 606 has separate memory access control restrictions and

may implement entirely unique memory access control logic. This forces an intruder to embark on multiple separate attacks to compromise each memory component 606.

[0063] The nonvolatile memory components 606 can employ either a separate physical and logical address range or a single contiguous address range since they are controlled and
5 programmed by the same microprocessor 602. Either implementation may suffice and would be appropriate as the system designer sees fit.

[0064] In addition, it is possible to share programming charge pumps and programming control between multiple nonvolatile memory components 606. If this is done, care may be taken to ensure that data and address lines of the individual nonvolatile memory component 606
10 are routed to the appropriate memory access control unit. In this case, the microprocessor 602 cannot provide control information that may lead to a subsequent attack of another memory component 606. Sharing the charge pumps may be preferred to ease timing and high voltage requirements of the entire chip/microcircuit within CAM 512.

[0065] There are many advantages to using a plurality of nonvolatile memory components 606
15 in a CAM 512. For example, the nonvolatile memory components 606 have physically separate address spaces and physical locations on the die. Further, each nonvolatile memory component 606 would have to be attacked and compromised separately. Separate memory control units can be implemented allowing each control unit to be uniquely customized and tailored to the specific memory module 606 being protected. This design requires each
20 nonvolatile memory component 606 to be attacked separately and individually. Therefore, the entire chip can withstand substantial external attack through the system I/O module 608. Accordingly, the use of such a plurality of nonvolatile memory components enables the protection of video, audio, broadband, and data/digital services reception.

[0066] FIG. 7 is a flow chart illustrating the use of multiple nonvolatile memory components in
25 accordance with one or more embodiments of the invention. At step 700, multiple nonvolatile memory components 606 are established in a CAM 512 (e.g., a smart card in an IRD 126). As described above, the nonvolatile memory components 606 are established in physically separate locations and are independently controlled. The components 606 may reside on a

single chip and may employ separate and unique address ranges or a single continuous address range. When on a single chip, charge pumps and programming control logic may be shared to ease high voltage and programming synchronization concerns. The CAM 512 may also include a volatile memory components 604, a custom logic block and a system input/output module

5 608.

[0067] At step 702, access to digital services is distributed among the plurality of nonvolatile memory components 606 along the system bus 610. At step 704, the nonvolatile memory components 606 are communicatively coupled to a microprocessor 602. The microprocessor is configured to use state information in the nonvolatile memory components 606 to provide

10 desired functionality and enforce one or more security policies for accessing the digital services.

Accordingly, each nonvolatile memory component 606 may have separate memory access control restrictions and may implement entirely unique memory access control logic. In other words, separate memory access control units can be designed and tailored to satisfy the functional requirements of each nonvolatile memory component 606. By controlling the memory 15 606 in physically separate locations and with logically separate security mechanisms, the integrity of the memory is thereby improved.

[0068] At step 706, digital services are accessed using the nonvolatile memory components 606 to provide desired functionality and enforce security policies for the access. Using the identified configuration with a plurality of nonvolatile memory components 606, if unauthorized 20 access is attempted, separate and independent attacks must be conducted on each nonvolatile memory component 606.

Conclusion

[0069] This concludes the description of one or more embodiments of the present invention.

25 The foregoing description of the invention has been presented for the purposes of illustration and description. It is not intended to be exhaustive or to limit the invention to the precise form disclosed. Many modifications and variations are possible in light of the above teaching.

20220729.02202

[0070] It is intended that the scope of the invention be limited not by this detailed description, but rather by the claims appended hereto. The above specification, examples and data provide a complete description of the manufacture and use of the composition of the invention. Since many embodiments of the invention can be made without departing from the spirit and scope of
5 the invention, the invention resides in the claims hereinafter appended.

2022.02.20 14:55:00